

NoSkid Foam

Material Description: NoSkid Foam is a closed-cell polyolefin foam coated with a specially formulated non-skid rubber on one side and a high tack pressure sensitive adhesive on the other. The adhesive makes it quick and economical to apply to your product and the non-skid properties keep your product in place. This foam is available in continuous rolls and cut pieces.



Product Information	Description
Carrier	Crosslinked Polyethylene
Adhesive	Rubber Based
Release Liner	Silicone coated paper
Application Temperature (°F)	65 to 100
Service Temperature (°F)	-20 to 175
Thickness (inch)	0.063

Foam	Typical Properties	Test Method
Color:	Black	Visual
Density (lb/ft ³):	2.5	ASTM D3575
Tensile Strength (psi) MD:	84	ASTM D3575
Elongation (% to break) MD:	160	ASTM D3575
Compression Deflection @25% (psi):	2.9	ASTM D3575
Compression Set @50% compression:	35	ASTM D3575

Adhesive	Typical Value	Test Method
180° Peel Adhesion (lb/in)	7.0 min	PSTC-101
Shear Adhesion (hours): 1in ² , 10lb, 72°F	25	PSTC-107
Quick Stick (lb/in):	5.5 min	PSTC-5

*Tests are performed on 2 mil PET

Storage

Tape should be stored within its' original packaging, in a dry place at Room Temperature (72°F). If room temperature is not possible, the storage temperatures should not exceed 39°F to 100°F. When the tape is stored under these conditions, the shelf life would be 18 months from the date of shipment.

Duraco provides this information and recommendations for informative purposes only. The data is intended as a guide only and is presented without guarantees and without assumption of liabilities resultant from the use of information provided.