

# Product Specification Sheet



## 4853

**Material Description:** High Performance double coated film tape with a BOPP liner that is ideal for applications where a hot knife is used. Ideal for bag enclosure tape and designed to tear films up to 3 mils thick.



Product Information		Description
Carrier		0.5mil PET
Adhesive		Rubber Based
Release Liner		BOPP
Application Temperature (°F)		65 to 100
Service Temperature (°F)		32 to 158
Adhesive and Carrier Thickness:		4.5 mils

  

Adhesive	Typical Value	Test Method
180° Peel (oz/in) - Liner side:	123	PSTC-101
180° Peel (oz/in) - Exposed side:	71	PSTC-101

\*Tests are performed on 2 mil PET

### Food Contact Information

Based on supplier information the components of the adhesive conform to the compositional requirements of FDA 175.105 for indirect food contact. Additional to this compliance there should also be a functional barrier between adhesive and the food. Such functional barrier and determination of suitability are the

### Storage

Tape should be stored within its' original packaging, in a dry place at Room Temperature (72°F). If room temperature is not possible, the storage temperatures should not exceed 39°F to 100°F. When the tape is stored under these conditions, the shelf life would be 18 months from the date of shipment.

Duraco provides this information and recommendations for informative purposes only. The data is intended as a guide only and is presented without guarantees and without assumption of liabilities resultant from the use of information provided.

[duraco.com](http://duraco.com)

7400 Industrial Drive, Forest Park, IL 60130 | Phone: (866) 800-0775 | [sales@duraco.com](mailto:sales@duraco.com)