

## Dubl Kote® 97 - 1/32"

**Material Description:** Dubl Kote® 97 is a double adhesive foam tape made with a high wet out rubber based adhesive. Bonds effectively to fabrics, corrugated, chipboard, and LSE plastics.



Product Information		Description	
Carrier		Crosslinked Polyethylene	
Adhesive		Rubber Based	
Release Liner		Silicone coated paper	
Application Temperature (°F)		65 to 100	
Service Temperature (°F)		0 to 158	
Thickness (inch)		0.031	

  

Foam	Typical Properties	Test Method
Color:	White / Black	Visual
Density (lb/ft³):	4.5 - 5.5	ASTM D3575
Tensile Strength (psi) MD:	226	ASTM D3575
Tensile Strength (psi) CD:	146	ASTM D3575
Elongation (% to break) MD:	284	ASTM D3575
Elongation (% to break) CD:	263	ASTM D3575
Compression Deflection @25% (psi):	8	ASTM D3575
Compression Set @50% compression:	7	ASTM D3575

  

Adhesive	Typical Value	Test Method
180° Peel Adhesion (lb/in)	9.0 min	PSTC-101
Shear Adhesion (hours): 1in², 10lb, 72°F	72	PSTC-107
Quick Stick (lb/in):	7.5 min	PSTC-5

\*Tests are performed on 2 mil PET

### Storage

Tape should be stored within its' original packaging, in a dry place at Room Temperature (72°F). If room temperature is not possible, the storage temperatures should not exceed 39°F to 100°F. When the tape is stored under these conditions, the shelf life would be 18 months from the date of shipment.

Duraco provides this information and recommendations for informative purposes only. The data is intended as a guide only and is presented without guarantees and without assumption of liabilities resultant from the use of information provided.